




Roval™ Partition Mounted Dual Access Sanitary Napkin Disposal

Feminine Hygiene Vendors and Disposals

Roval

MasterFormat Section 10 28 13



Scan for Information



SUSTAINABILITY/LEED

MR 4.1 (1) MR 6 (1) EQ 4.2 (1)
MR 4.2 (1) EQ 4.1 (1) EQ 4.4 (1)

NOTE:
ALL DIM'S INCH [MM]
ILLUSTRATION FOR REF ONLY AND NTS

PRODUCT OVERVIEW

Heavy-duty 9/64" [3,6] staked piano hinge adds to the robust construction. Drawn one-piece seamless door of 22 gauge type 304 stainless steel with a satin finish. 1.0 gal. (3.8 L) waste capacity. Same as 20470 but mounts through partitions up to 1-1/4" [32] thick. Expandable steel waste can ensures a perfect fit for thicker partitions. Users push door to deposit waste material into receptacle. Push-door is self-closing. Empty refuse manually on a cycle determined by maintenance needs by removing waste container and inverting over collection bag. Hemmed edges on waste container provide safety for service. Locked door prevents unauthorized access or removal. Full face door shall be fabricated of 22 gauge type 304 stainless steel alloy 18-8. with no exposed fastening devices or spot-welded seams.

KEY FEATURES & SPECIFICATIONS

- Curved front adds strength and elegance
- Concealed, Multi-Staked Piano Hinge - Removable Waste Can
- Type 304 Stainless Steel - Satin Finish
- Partition Mounted
- Dual Access Self-Closing push door
- 1.0 Gal. (3.7 L) Waste Capacity

OPERATION & MAINTENANCE

Users push door to deposit waste material into receptacle. Push-door is self-closing. Empty refuse by removing waste container and inverting over collection bag. Safety finger grip on waste container provides convenient grip for service. Locked door prevents unauthorized access or removal.

TECHNICAL INFORMATION / PRODUCT PROPERTIES

Property	Value
Dimensions	12-13/16" [325] W x 11" [280] H
Construction	Type 304 Stainless Steel - Satin Finish
Mounting	Partition Mounted
Capacity	1.0 Gal. (3.7 L) Waste Capacity

INSTALLATION

Suit partition thickness. For compliance with 2010 ADA Accessibility Standards install unit so that top of waste receptacle door is 48" [1219] maximum Above Finished Floor (AFF) if clear floor reach access is provided. For general utility install unit with bottom edge 44-3/16" [1123] AFF. Note that top of Partition Cut Out (PCO) is 7/8" [23] below top of frame.

Partition Cut Out (PCO) required is 11" [280] W x 9-1/4" H [235] x 1/2" [13] to 1-1/4" [32] Thick

WARRANTY

One (1) Year from date of Invoice