

**Simplicity™ Collection Paper Towel Dispenser (Multi, C-Fold) – Surface Mounted**


Paper Towel Dispensers

Simplicity

MasterFormat Section 10 28 13



Scan for Information



**SUSTAINABILITY/LEED**

MR 4.1 (1) MR 6 (1) EQ 4.2 (1)  
MR 4.2 (1) EQ 4.1 (1) EQ 4.4 (1)

**NOTE:**  
ALL DIM'S INCH [MM]  
ILLUSTRATION FOR REF ONLY AND NTS  
FOR CLEANING INSTRUCTIONS SEE APPROPRIATE SECTIONS IN  
PRODUCT CARE & MAINTENANCE BULLETIN (PCM) ON ASI WEBSITE

**PRODUCT OVERVIEW**

Holds and dispenses 600 C-fold or 800 multi-fold paper towels. Door held closed with a tumbler lock. All exposed surfaces have a satin finish. Surface mounted with 9" [229] stainless steel collar. Towels are self-feeding until supply is depleted. Unit may be reloaded with a partial load in-place and will continue to feed properly. Locking door prevents unauthorized access or removal.

**KEY FEATURES & SPECIFICATIONS**

- Seamless construction, crisp lines and minimalistic design
- Concealed multi-staked hinge - 3/16" diameter [Ø5]
- Type 304 Stainless Steel - Satin Finish
- Surface Mounted - w/ 9" Collar
- 600 C-Fold OR 800 Multi-Fold

**OPERATION & MAINTENANCE**

Towels are self-feeding until supply is depleted. Unit may be reloaded with a partial load in-place and will continue to feed properly. Locking door prevents unauthorized access or removal.

**TECHNICAL INFORMATION / PRODUCT PROPERTIES**

Property	Value
Dimensions	14-1/4" [362] W x 28" [711] H x 4-1/2" [114] D
Construction	Type 304 Stainless Steel - Satin Finish Concealed multi-staked hinge - 3/16" Dia. [Ø5]
Power	N/A
Operation	Manual - Pull Type
Mounting	Surface Mounted - w/ 9" Collar
Capacity	600 C-Fold OR 800 Multi-Fold

**INSTALLATION**

Surface mount unit to wall using four (4) #10 self-threading screws (by others) through concealed mounting holes in cabinet back. For compliance with 2010 ADA Accessibility Standards install unit so that centerline of towel dispenser slot is 48" [1219] maximum above finished floor (AFF). SM collar is installed on cabinet prior to mounting to wall following procedure described on SM Collar Data Sheet.

**WARRANTY**

One (1) Year from date of Invoice