

Spare Roll Toilet Tissue Holder - Recessed, Satin Finish

Toilet Tissue Dispensers

MasterFormat Section 10 28 13









Sustainability/LEED

MR 4.1 (1) MR 6 (1) EQ 4.2 (1) MR 4.2 (1) EQ 4.1 (1) EQ 4.4 (1)

6-5/16" [160] 4" [102] 7/32" DIA [Ø5,6] 5-1/16" [129] 1-1/2" TWO (2) HOLES [16] EACH SIDE [38] 1-1/2" 6-1/4" [38] [159] 5-1/4" [133] 4-3/4' Χ [121] 5-1/4" [133] 1-1/2" [38] 1 2-13/16" 3/4" [71] [19] TYP

NOTE:
ALL DIM'S INCH [MM]
ILLUSTRATION FOR REF ONLY AND NTS

PRODUCT OVERVIEW

Satin Finish. Holds two (2) rolls and dispenses one (1) roll at a time of standard core roll toilet paper up to 5-1/8" diameter [Ø130] rolls. Box holds one (1) extra toilet paper roll in reserve. Spring-loaded roller is chrome plated high impact resistant ABS plastic and revolves freely. Reserve roll is protected from access until roll in-use is completely exhausted. Spring-loaded spindle holds roll until core is removed. All exposed surfaces are satin or bright finish as chosen by option and indicated by code suffix. Model Option Notes: 7403-B – Bright finish 7403-S – Satin finish

KEY FEATURES & SPECIFICATIONS

- Spare Toilet Roll Holder
- Type 304 Stainless Steel Satin Finish
- Recessed

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model:#7403-S

Revision: R2 Issued: 11/1/2021 Revised: 5/29/2023

CSI: 10 28 13 Toilet Accessories Page: 1 of 2

Page: 2 of 2



OPERATION & MAINTENANCE

Spindle revolves freely. Reserve roll is protected from access until roll in-use is completely exhausted. Spring-loaded spindle holds roll until core is removed. Service staff replaces reserve roll on a cycle determined by maintenance needs.

TECHNICAL INFORMATION / PRODUCT PROPERTIES

Property	Value
Dimensions	6-5/16" [160] W x 6-1/4" [160] H x 6-13/16" [173] D
Construction	Type 304 Stainless Steel - Satin Finish
Mounting	Recessed
Capacity	Holds two (2) rolls and dispenses one (1) roll at a time of standard core roll toilet paper up to 5-1/8" diameter [Ø130] rolls

INSTALLATION

Insert into RWO and mount unit in wall recess using #10 stainless steel Philips flat or oval head self-threading screws or wood

Rough Wall Opening (RWO) required is 5-1/2" [140] W x 5-1/2" [140] H x 4" [102] D minimum

OPTIONS

WARRANTY

CSI:10 28 13

One (1) Year from date of Invoice

Toilet Accessories

American Specialties, Inc. 441 Saw Mill River Road, Yonkers, NY 10701 (914) 476-9000 | www.americanspecialties.com Model: #7403-S Revision: R2 Issued: 11/1/2021 Revised: 5/29/2023